SYM	NO REQ'D	DESCRIPTION	DWG NO
1	1	COMB. POKE HOLE/INSPECT. WINDOW	12543-2

1-G (TYP.)

60" I.D.

(36)-½" DIA HOLES EQ. SPACED (STRADDLE ℄)

TWO 4"Ø OR FOUR 5"Ø MAY BE USED AS SHOWN. MAX. VOLUME 800 CFM

6" SCH 40 PIPE - 8" LONG (ONE REQ'D)

12"

℄ DSCHG.

℄ ENTRY

(TYP.)

45° (TYP.)

4" SCH. 40 PIPE - 8" LG. (STD. SINGLE SYS.)

2"×2"×¼" ROLLED ∠

62¼" DIA. B.C.

TANK BAFFLE W/WEAR PLATE SEE DETAIL "B"

TANK COVER. SEE DETAIL "A"

NOTE

USE JM Nº 107-⅛" THK RUBBER SHEET FOR GASKETING MTL TO SPLICE CUT JOINT ON DIAGONAL

14 GA. CAP

TANK OF ⅜" STL. P -WELDED CONSTR.

TANK

COPE PIPE TO FIT AS SHOWN

2"

℄ LEG

(TYP - 4 PLACES)

4" SCH 40 PIPE (4 REQ'D.)

SECT A-A

8"

8"

12"

1'-8" (TYP.)

5'-0"

(TYP.

8" I.D.

8"

8"

9'-5"

8" ROTARY VALVE

5'-6"

(TYP

SEE DETAIL "C"

FACTORY FLOOR

NOTE

INSURE AGAINST WARPAGE IN WELDING Es TO COVER

⅜" THK. STL. P

62¼" DIA. B.C.

64" DIA

E3 - 5.0 × 4'-9" LG. (TWO REQ'D.)

2'-4"

(TYP.

1'-2"

DETAIL A

COVER

⅜" STL. BAFFLE

⅜"

⅝"

1-G (TYP.)

10 GA. WEAR PLATE (REMOVABLE)

10 GA. BRACKET (TYP - 3 SIDES)

2'-4¾"

1'-3⅝"

⅜"

28" - 25" - 10 GA. WEAR PLATE (SLIDES UP FOR REMOVAL)

2'-1"

5'-0"

⅜" STL PLATE

5'-0"

DETAIL B

BAFFLE

½" STL. PLATE

2¾"

2¾"

7"

⅝"Ø HOLE - 2 PLACES

5½"

7"

DETAIL C

PLATE - 4 REQ'D.

DUST TRAP VACUUM SYSTEM

TOLERANCES UNLESS OTHERWISE NOTED FRACTIONAL DIMENSIONS ± DECIMAL DIMENSIONS ±

41	42	43	44	45	46	47	48	49	50	51	52
	E		I							D	F

C5

Published by AsbestosClaims.Law
asbestosclaims.law/library/25181/1